DERWENT-ACC-NO:

1983-17998K

DERWENT-WEEK:

198308

COPYRIGHT 2005 DERWENT INFORMATION LTD

TITLE:

Thermally insulating roller blind - with foam

core

between fabric and metallised film covers

INVENTOR: AUVIN, G; LESCH, H; SCHMUCK, J C

PATENT-ASSIGNEE: SIRS REV SOL SOC IN[SIRSN] , SOC INT

REVETEMENTS [ITREN]

PRIORITY-DATA: 1981FR-0013569 (July 3, 1981)

PATENT-FAMILY:

PUB-NO PUB-DATE LANGUAGE

PAGES MAIN-IPC

FR 2508969 A) January 7, 1983 N/A

008 N/A

DE 3224851 A March 17, 1983 N/A

000 N/A

INT-CL (IPC): A47H023/02, B32B015/20, B32B027/36, E06B009/24

ABSTRACTED-PUB-NO: FR 2508969A

BASIC-ABSTRACT:

A thermally insulating roller blind has an interlayer of open celled acrylic

foam between one cover of non-woven fabric and one cover of polyester film

<u>lined with aluminium</u> on one or both faces. Esp. suitable for industrial

applications, to reduce heat losses via windows. The blind may be reinforced

by a layer of net between the polyester film and the foam core layer: the net

pref. being of glass strands.

Specifically claims such blinds where the relative density of the core layer is

0.05-0.15, pref. about 0.08 and the non-woven cover is made of hollow polyester

fibres (RTM - "Holofibres") rated at 3.3 and/or 6.7 dtex to a

grammage of 60-300, pref. 140-200 g/sq.m.

The polyester film is 0.8-30, pref. 16-20 microns thick, may be covered with aluminium either by coating or by lamination to foil.

The layers may be prefabricated and laminated by calendering, or may be

assembled using the foam layer prior to drying. Example blinds are 3 mm thick

overall, weighed 340 g/sq. m, had tensile strengths of 4-8 kg/cm, extensibility to break of 3-4% and a thermal conductivity of 0.22-0.38 sq. m.

deq. C/W, depending on the method of test.

TITLE-TERMS: THERMAL INSULATE ROLL BLIND FOAM CORE FABRIC METALLISE FILM COVER

DERWENT-CLASS: A93 P27 P73 Q48

CPI-CODES: A04-F01; A05-E01; A12-R02; A12-R06; A12-S04B;

POLYMER-MULTIPUNCH-CODES-AND-KEY-SERIALS:

Key Serials: 0011 0231 0486 0487 1291 3178 1319 1462 2214 2386 2416 2434 2437

2439 2498 2513 2528 3245 2539 2635 2646 2654 2665 3258 2692 2697 2720 2723 2724

2726 2728 2820

Multipunch Codes: 013 034 04- 074 081 143 144 155 163 166 169 170 171 274 308

309 402 408 409 430 431 435 440 441 443 47& 471 477 481 483 491 493 50& 551 56&

567 573 575 581 596 604 606 613 617 651 664 665 688 723

SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C1983-017551 Non-CPI Secondary Accession Numbers: N1983-033221

